

Hooked Fork



Hooked Fork

Material: Copper
Insulation: Polyvinyl Chloride
 UL approval E100455
 CSA approval 093995
 RoHS compliant

Max. elec. rating: ■ 19 amp
 ■ 27 amp
 ■ 48 amp
 600 volts 75°C

Wire Range mm ² (AWG)	Part No.	Dimensions mm									Vibration Resistant
		D1	D2	D3	D4	L	L1	H1	H2	T	
● 0.5-1.5 (22 - 16)	37RHF	1.8	3.7	7.8	4.3	14.8	10.0	10.8	5.5	0.8	37RHF-VR
	43RHF	1.8	4.3	7.8	4.3	14.9	10.0	10.9	5.5	0.8	43RHF-VR
	53RHF	1.8	5.3	7.8	4.3	15.3	10.0	11.3	5.5	0.8	53RHF-VR
● 1.5-2.5 (16 - 14)	37BHF	2.3	3.7	7.8	4.8	15.3	10.0	11.3	5.5	0.8	37BHF-VR
	43BHF	2.3	4.3	7.8	4.8	15.1	10.0	11.1	5.5	0.8	43BHF-VR
	53BHF	2.3	5.3	7.8	4.8	15.8	10.0	11.8	5.5	0.8	53BHF-VR
● 4-6 (12 - 10)	37YHF	3.5	3.7	8.4	6.5	20.1	13.5	14.0	6.5	0.8	37YHF-VR
	43YHF	3.5	4.3	8.4	6.5	21.0	13.5	14.0	6.5	0.8	43YHF-VR
	53YHF	3.5	5.3	8.4	6.5	21.3	13.5	14.3	6.5	0.8	53YHF-VR

Pack Quantity: 100

