

## Ring Terminals

## Fork Terminals



### Ring Terminals

**Material:** Copper

**Insulation:** Polyvinyl Chloride


**Max. elec. rating:** ■ 19 amp  
■ 27 amp  
■ 48 amp

600 volts 75°C

UL approval E100455

CSA approval 093995

RoHS compliant



Standard

Vibration Resistant

### Fork Terminals

**Material:** Copper

**Insulation:** Polyvinyl Chloride


**Max. elec. rating:** ■ 19 amp  
■ 27 amp  
■ 48 amp

600 volts 75°C

UL approval E100455

CSA approval 093995

RoHS compliant



Standard

Vibration Resistant

Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions mm						Vibration Resistant
		D1	D3	D4	L	L1	D2	
●	32RER	1.8	5.5	4.3	13.7	10	3.2	32RER-VR
	37RER	1.8	6.6	4.3	15.5	10	3.7	37RER-VR
	43RER	1.8	8.0	4.3	16.2	10	4.3	43RER-VR
	53RER	1.8	8.0	4.3	16.7	10	5.3	53RER-VR
	65RER	1.8	11.0	4.3	20.4	10	6.5	65RER-VR
0.5-1.5 (22 - 16)	85RER	1.8	12.0	4.3	20.2	10	8.5	85RER-VR
	10RER	1.8	14.5	4.3	25.1	10	10.0	10RER-VR
	32BER	2.3	5.5	4.8	15.5	10	3.2	32BER-VR
●	37BER	2.3	6.6	4.8	15.6	10	3.7	37BER-VR
	43BER	2.3	6.6	4.8	15.9	10	4.3	43BER-VR
	53BER	2.3	8.0	4.8	16.9	10	5.3	53BER-VR
	65BER	2.3	10.5	4.8	20.8	10	6.5	65BER-VR
	85BER	2.3	12.0	4.8	21.4	10	8.5	85BER-VR
1.5-2.5 (16 - 14)	10BER	2.3	14.5	4.8	23.6	10	10.0	10BER-VR
●	32YER	3.5	7.2	6.5	22.2	13.5	3.2	32YER-VR
	37YER	3.5	7.2	6.5	22.2	13.5	3.7	37YER-VR
	43YER	3.5	7.2	6.5	22.2	13.5	4.3	43YER-VR
	53YER	3.5	9.5	6.5	22.2	13.5	5.3	53YER-VR
	65YER	3.5	11.0	6.5	23.5	13.5	6.5	65YER-VR
4-6 (12 - 10)	85YER	3.5	14.0	6.5	27.0	13.5	8.5	85YER-VR
	10YER	3.5	15.0	6.5	30.0	13.5	10.0	10YER-VR
	12YER	3.5	19.0	6.5	30.0	13.5	13.0	12YER-VR

Pack Quantity: 100

Wire Range mm <sup>2</sup> (AWG)	Part No.	Dimensions mm						Vibration Resistant
		D1	D3	D4	L	L1	D2	
●	32RF	1.8	5.7	4.3	15.3	10	3.2	32RF-VR
	37RF	1.8	6.4	4.3	15.3	10	3.7	37RF-VR
	43RF	1.8	6.4	4.3	15.8	10	4.3	43RF-VR
	53RF	1.8	7.5	4.3	16.4	10	5.3	53RF-VR
	65RF	1.8	8.5	4.3	19.7	10	6.5	65RF-VR
0.5-1.5 (22 - 16)	32BF	2.3	6.0	4.8	16.0	10	3.2	32BF-VR
●	37BF	2.3	6.4	4.8	15.7	10	3.7	37BF-VR
	43BF	2.3	6.4	4.8	16.1	10	4.3	43BF-VR
	53BF	2.3	8.5	4.8	16.2	10	5.3	53BF-VR
1.5-2.5 (16 - 14)	65BF	2.3	11.0	4.8	20.1	10	6.5	65BF-VR
●	32YF	3.5	5.8	6.5	18.5	13.5	3.2	32YF-VR
	37YF	3.5	6.4	6.5	20.8	13.5	3.7	37YF-VR
	43YF	3.5	7.1	6.5	21.0	13.5	4.3	43YF-VR
	53YF	3.5	9.5	6.5	21.6	13.5	5.3	53YF-VR
	65YF	3.5	12.0	6.5	24.9	13.5	6.5	65YF-VR
4-6 (12 - 10)	85YF	3.5	14.0	6.5	28.0	13.5	8.5	85YF-VR
	10YF	3.5	18.0	6.5	28.0	13.5	10.0	10YF-VR

Pack Quantity: 100

